

MEZGER Heftsysteme GmbH

Saganer Straße 24 Postfach (P.O.B.) 551170 D-90475 Nürnberg D-90218 Nürnberg

Tel. +49 911 98494-0 Fax +49 911 98494-30 Mail info@mezger.eu Internet www.mezger.eu

Applications for Blind Stapling Heads E 22, E 24, E 26

Info to Pos. 5 page 1 of 2 312

Blind Stapling Head E for 4000 Coiled Staples TOP E

Complete pneumatic blind stapling unit with automatic feed travel for stationary applications in stapling devices and special purpose machines.

Blind Stapling Heads E are especially suited for the automatic closure of filled folding boxes. Blind stapling means that the staple is automatically clinched within the under board without penetrating completely through.





Box bottom and top stapling of filled cartons

A 1-2 Automatic Stapling Machine SHM E 24-60/4 with 2 heads for bottom and 2 for top stapling

Simultaneous stapling of bottoms and lids of filled folding boxes made from corrugated cardboard in differing sizes.



Top stapling of cartons with overlapping flaps

A 1-2 Stapling Automat E 24-60/2 TN with 2 Heads

Folding boxes with the same size and with overlapping flaps which have already been bottom-stapled and filled will be centred on a conveyor belt and fed into the folding station. The top flaps still being open will be folded automatically.

After folding the box will be conveyed into the stapling station where 2 stapling heads E 24 apply 2 - 4 staples according to the box size. Capacity up to 8 boxes / minute.







Top closure of telescopic-type boxes

A 1-2 Stapling Automat SHM E 24-60/4SX

The boxes are introduced one after the other into the stapling device. The size of the boxes are automatically detected. The motorized roller conveyor stops the box at the stapling position. A lifting device elevates the box into the stapling position of the stapling heads and the 4 x stapling is released.

The staples are positioned concentric at all four sides of the box. Capacity 6 - 7 boxes / minute.





