

TOP STAPLERS

MEPA 18 / 18 P + 22 / 22 P



APPLICATION RANGE

Closing filled boxes made from corrugated cardboard with joining and overlapping flaps using clinching anvils. Suitable for single and double corrugated cardboard and thin triple corrugated cardboard. The staple form can be changed from an open to a closed stapling. The penetration depth of the staple is adjustable.

TECHNICAL DATA

Mechanical or pneumatic staplers for staple series B 5/8, B 3/4 und B 7/8, leg length 15 – 22 mm. Sound suppressor. Clinching anvils return automatically.

ТҮРЕ	MEPA 18	MEPA 22	MEPA 18 P	MEPA 22 P
Version	mechanical	mechanical	pneumatic	pneumatic
Device dimensions (length x width x height)	380 x 115 x 295 mm	380 x 115 x 295 mm	340 x 115 x 225 mm	340 x 115 x 225 mm
Weight	1.74 kg	1.74 kg	1.98 kg	2.16 kg
Leg length of the staples	15, 18 mm	18, 22 mm	15, 18 mm	18, 22 mm
Load capacity: (Number of staples)	100	100	100	100
Air pressure	-	-	4 – 6 bar	4 – 6 bar
Air consumption per stapling process at 6 bar	-	-	0.7 NL	0.7 NL







